

**DESCRIPTION**


- ELECTRONIC BALLAST
- ELECTRONIC TRANSFORMER
- SWITCH MODE POWER SUPPLY

**FEATURES:**

- LOW THERMAL RESISTANCE
- HIGH INPUT RESISTANCE
- FAST SWITCHING
- ROHS COMPLIANT

**MAXIMUM RATINGS (T<sub>c</sub>=25°C)**

PARAMETER	SYMBOL	VALUE	UNIT
Drain-source Voltage	VDS	100	V
gate-source Voltage	VGS	±20	V
Continuous Drain Current (T <sub>C</sub> =25°C)	ID	57	A
Drain Current-Pulsed	IDM	195	A
Total Dissipation	PD	172	W
Junction Temperature	T <sub>j</sub>	175	°C
Storage Temperature	T <sub>stg</sub>	-55-175	°C
Single Pulse Avalanche Energy (L=0.5mH)	EAS	115	mJ

**MECHANICAL**

**ELECTRONIC CHARACTERISTICS (T<sub>c</sub>=25°C)**

CHARACTERISTICS	SYMBOL	TEST CONDITION	MIN	MAX	UNIT
Drain-source Breakdown Voltage	BVDSS	VGS=0V, ID=250 μA	100		V
Gate Threshold Voltage	VGS (TH)	VGS=VDS, ID=250 μA	2	4	V
Drain-source Leakage Current	IDSS	VDS=100V, VGS=0V		1	uA
Drain-Source Diode Forward Voltage	VSD	VGS=0V, IS=30A		1.2	V
Gate-body Leakage Current (VDS = 0)	IGSS	VGS=±20V		±100	nA
Static Drain-source On Resistance	RDS (ON)	VGS=10V, ID=30A		16	mΩ
Thermal Resistance Junction-case	RthJ-c			0.88	°C/W

**■ DYNAMIC CHARACTERISTICS (T<sub>c</sub>=25°C)**







CHARACTERISTICS	SYMBOL	TEST CONDITION	MIN	TYP	MAX	UNIT
Input Capacitance	C <sub>iss</sub>	V <sub>gsAcFreq</sub> =1.0MHz, V <sub>dsDc</sub> =25V	-	2500	-	pF
output Capacitance	C <sub>oss</sub>		-	260	-	pF
Reverse Transfer Capacitance	C <sub>rss</sub>		-	100	-	pF

**■ SWITCHING CHARACTERISTICS (T<sub>c</sub>=25°C)**




CHARACTERISTICS	SYMBOL	TEST CONDITION	MIN	TYP	MAX	UNIT
Turn-On Delay Time	t <sub>d(on)</sub>	V <sub>DD</sub> =40V, I <sub>D</sub> =30A V <sub>GS</sub> =10V, R <sub>G</sub> =2.5Ω	-	16	-	ns
Turn-On Rise Time	t <sub>r</sub>		-	71	-	ns
Turn-Off Delay Time	t <sub>d(off)</sub>		-	43	-	ns
Turn-Off Rise Time	t <sub>f</sub>		-	72	-	ns
Total Gate Charge	Q <sub>g</sub>	V <sub>DS</sub> =40V, I <sub>D</sub> =30A, V <sub>GS</sub> =10V	-	42	-	nC
Gate-Source Charge	Q <sub>gs</sub>		-	12	-	nC
Gate-Drain Charge	Q <sub>gd</sub>		-	11.4	-	nC

**■ DRAIN-SOURCE DIODE MAXIMUM RATINGS AND CHARACTERISTICS (T<sub>c</sub>=25°C)**

CHARACTERISTICS	SYMBOL	TEST CONDITION	MIN	TYP	MAX	UNIT
Diode Forward Voltage	V <sub>SD</sub>	V <sub>GS</sub> =0V, I <sub>S</sub> =30A	-	-	1.2	V
Reverse Recovery Time	t <sub>rr</sub>	V <sub>GS</sub> =0V, I <sub>S</sub> =57A, dI <sub>F</sub> /dt=100A/μs	-	124	-	ns
Reverse Recovery Charge	Q <sub>rr</sub>		-	146	-	nC

**CHARACTERISTICS CURVE**

**Output Characteristic**

**Transfer Characteristic**

**On Resistance Vs Drain Current**

**Safe Operation Area**

**On Resistance Vs Junction Temperature**

**Capacitance**

■ CHARACTERISTICS CURVE





### TO-220 MECHANICAL DATA

UNIT: mm

SYMBOL	MIN	NOM	MAX	SYMBOL	MIN	NOM	MAX
A	4		4.8	e	2.44	2.54	2.64
B	1.2		1.4	F	1.1		1.4
B1	1		1.4	L	12.5		14.5
b1	0.75		0.95	L1	3	3.5	4
c	0.4		0.55	ΦP	3.7	3.8	3.9
D	15		16.5	Q	2.5		3
D1	5.9		6.9	Q1	2		2.9
E	9.9		10.7				

